

Hot water on tap all day, every day. Leda Electric Storage.



- Full "Mains Pressure" to all taps
- Dual handed for easy installation
- Indoor and outdoor use
- Leda "Longlife" vitreous enamel tanks,
- Designed to maximise life and durability
- Leda 7 year warranty including 1 year full parts and labour
- Leda proudly Australian



For further information, visit www.ledaaustralia.com or call 1800 697 652

S O L A R ■ C O N T I N U O U S G A S ■ E L E C T R I C S T O R A G E

Leda

Leda Electric Storage Specifications

Model No		LE801	LE1251	LE1602	LE2503	LE3153	LE4003
Hot water delivery	Litres	80	125	160	250	315	400
Tank Capacity	Litres	95	142	200	270	340	450
Recommended Expansion Control Valve (ECV)	kpa	850	850	850	850	850	700
Maximum Supply Pressure	kpa	600	600	600	600	600	600
Pressure and Temperature Relief Valve (PTRV)	kpa	1000	1000	1000	1000	850	850
Element Rating	Kw	1.8	1.8	2.4	3.6	3.6	3.6
Thermostat Setting (Max)	Deg °C	70	70	70	70	70	70
Weight (Empty)	kg	35	45	65	80	95	130
Measurements							
A - Height	mm	1033	1482	1484	1388	1690	1709
B - Diameter	mm	470	470	540	648	648	730
C - Inlet Height	mm	82	82	82	82	82	82
D - Outlet Height	mm	852	1303	1300	1175	1478	1472
E - Power Connection Point	mm	81	81	89	131	131	151
F - Element Angle	Deg	23	23	23	32	32	30
Warranty (Cylinder)	Years	7	7	7	7	7	7
Warranty (Parts and Labor)	Years	1	1	1	1	1	1
Dual Handed Fittings		Yes	Yes	Yes	Yes	Yes	Yes
PTR Valve Fitting	mm	15	15	15	15	15	15
Inlet and Outlet Fittings	mm	20	20	20	20	20	20

